



复 合 支 柱 绝 缘 子
POLYMER POST INSULATOR

Figure No	Catalogue Type	Rated Voltage (KV)	Specified Mechanical bending Load(KN)	Section Length (mm)	Min Arc Distance (mm)	Min creepage Distance (mm)	Lightning Withstand Voltage(KV)	Wet power frequency Voltage (KV)
1	FZSW-10/4	10	4.0	254±1.0	145	400	95	40
2	FZSW-10/6	10	6.0	261±1.0	161	432	75	42
3	FZSW-10/6	10	6.0	281±1.0	186.5	432	75	42
4	FZSW-12/4	12	4.0	254±1.0	145	400	95	40
5	FZSW-12/6	12	6.0	281±2.0	161	432	75	42
6	FZSW-12/6	12	6.0	281±2.0	186.5	432	75	42
7	FZSW-20/4	20	4.0	370±1.0	260	580	145	50
8	FZSW-24/4	24	4.0	370±1.0	260	580	145	50
9	FZSW-40.5/4	40.5	4.0	560±1.0	450	1050	230	95
10	FZSW-35/4	35	4.0	560±1.0	450	1050	230	95

Address: NO.283 Xiao Shan Road,Economic&Technical Development Zone, Qingdao

TEL:+86-532-80986697

FAX:+86-532-80986697

Website:www.cosinelectric.com Email:info@cosinelectric.com